

Safety Data Sheet

Ultramid® C33

Revision date : 2021/09/21
Version: 3.0

Page: 1/8
(30509850/SDS_GEN_CA/EN)

1. Identification

Product identifier used on the label

Ultramid® C33

Recommended use of the chemical and restriction on use

Recommended use*: Polymer; for industrial processing only
Suitable for use in industrial sector: Polymers industry
Unsuitable for use: Not intended for sale to or use by the general public.

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF Canada Inc.
5025 Creebank Road
Building A, Floor 2
Mississauga, ON, L4W 0B6, CANADA

Telephone: +1 289 360-1300

Emergency telephone number

24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300
BASF HOTLINE: (800) 454-COPE (2673)

Other means of identification

Chemical family: Preparation based on: polyamide

2. Hazards Identification

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

Classification of the product

No need for classification according to GHS criteria for this product.

Label elements

Safety Data Sheet

Ultramid® C33

Revision date : 2021/09/21
Version: 3.0

Page: 2/8
(30509850/SDS_GEN_CA/EN)

The product does not require a hazard warning label in accordance with GHS criteria.

3. Composition / Information on Ingredients

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

Under the referenced regulation, this product does not contain any components classified for health hazards above the relevant cut off value.

4. First-Aid Measures

Description of first aid measures

General advice:

Remove contaminated clothing.

Burns caused by molten material require hospital treatment.

If inhaled:

Assist in breathing if necessary. Keep patient calm, remove to fresh air. Seek medical attention.

If on skin:

Burns caused by molten material require hospital treatment. Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.

If in eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

If swallowed:

Ingestion is not likely in the available physical form. If ingested, seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: (Further) symptoms and / or effects are not known so far

Hazards: No hazard is expected under intended use and appropriate handling.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:

water spray, foam, dry powder, carbon dioxide

Safety Data Sheet

Ultramid® C33

Revision date : 2021/09/21
Version: 3.0

Page: 3/8
(30509850/SDS_GEN_CA/EN)

Unsuitable extinguishing media for safety reasons:
No data available.

Special hazards arising from the substance or mixture

Hazards during fire-fighting:

carbon monoxide, hydrogen cyanide, can be emitted at > 300 °C

Under special fire conditions traces of other toxic substances are possible. Formation of further decomposition and oxidation products depends upon the fire conditions.

Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental release measures

Further accidental release measures:

High risk of slipping due to leakage/spillage of product.

Personal precautions, protective equipment and emergency procedures

No special precautions necessary.

Environmental precautions

Methods and material for containment and cleaning up

For small amounts: Pick up with suitable appliance and dispose of.

For large amounts: Pick up with suitable appliance and dispose of.

7. Handling and Storage

Precautions for safe handling

Protection against fire and explosion:

Take precautionary measures against static discharges.

Conditions for safe storage, including any incompatibilities

Suitable materials for containers: Stainless steel 1.4301 (V2), Stainless steel 1.4401, Aluminium, High density polyethylene (HDPE)

Storage stability:

Protect against moisture.

8. Exposure Controls/Personal Protection

No occupational exposure limits known.

Advice on system design:

Provide local exhaust ventilation to control dusts/vapours.

Safety Data Sheet

Ultramid® C33

Revision date : 2021/09/21

Version: 3.0

Page: 4/8

(30509850/SDS_GEN_CA/EN)

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) particulate respirator. Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

Hand protection:

Wear gloves to prevent contact during mechanical processing and/or hot melt conditions.

Eye protection:

Safety glasses with side-shields.

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Wear protective clothing to prevent contact during mechanical processing and/or hot melt conditions. Avoid inhalation of dust. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and Chemical Properties

Form:	pellets	
Odour:	odourless	
Odour threshold:	not applicable	
Colour:	white, translucent	
pH value:	not soluble	
Melting temperature:	approx. 191 - 197 °C	
Freezing point:	No data available.	
Melting point:	No data available.	
onset of boiling:	not applicable	
Boiling point:	No data available.	
Boiling range:	No data available.	
Sublimation point:	No applicable information available.	
Flash point:	not applicable, the product is a solid	
Flammability:	not highly flammable	
Lower explosion limit:	For solids not relevant for classification and labelling.	
Upper explosion limit:	For solids not relevant for classification and labelling.	
Autoignition:	> 400 °C	(ASTM D1929)
Vapour pressure:	not applicable	
Density:	1.12 - 1.15 g/cm ³ (20 °C)	(EN ISO 1183-1)
Relative density:	No data available.	
Bulk density:	690 - 790 kg/m ³	
Vapour density:	not applicable, The product is a non-volatile solid.	
Partitioning coefficient n-octanol/water (log Pow):	not applicable	
Self-ignition temperature:	not self-igniting	
Thermal decomposition:	> 300 °C May decompose if overheated and/or subjected to prolonged heating.	
Viscosity, dynamic:	not applicable, the product is a solid	
Solubility in water:	insoluble	
Evaporation rate:	not applicable, The product is a non-volatile solid.	

Safety Data Sheet

Ultramid® C33

Revision date : 2021/09/21
Version: 3.0

Page: 5/8
(30509850/SDS_GEN_CA/EN)

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:

No corrosive effect on metal.

Oxidizing properties:

not fire-propagating

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

No hazardous reactions known.

Conditions to avoid

Temperature: > 300 degrees Celsius

Avoid prolonged exposure to extreme heat.

Incompatible materials

No substances known that should be avoided.

Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: carbon monoxide, hydrogen cyanide, caprolactam

Thermal decomposition products: caprolactam, The substances/groups of substances mentioned may be released during processing.

Thermal decomposition:

> 300 °C

May decompose if overheated and/or subjected to prolonged heating.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Contact with molten product may cause thermal burns. The resin in pelleted form poses a low hazard.

Inhalation

Type of value: ATE

Value: > 5.0000 mg/l

Determined for dust

Dermal

Safety Data Sheet

Ultramid® C33

Revision date : 2021/09/21
Version: 3.0

Page: 6/8
(30509850/SDS_GEN_CA/EN)

Type of value: ATE
Value: > 5,000 mg/kg

Irritation / corrosion

Assessment of irritating effects: Thermal decomposition products of the substance can irritate the eyes, skin, and respiratory tract.

Sensitization

Assessment of sensitization: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Aspiration Hazard

not applicable

Chronic Toxicity/Effects

Genetic toxicity

Assessment of mutagenicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Other Information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Medical conditions aggravated by overexposure

Data available do not indicate that there are medical conditions that are generally recognized as being aggravated by exposure to this substance/product. See SDS section 11 - Toxicological information.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The product has not been tested. The statement has been derived from the structure of the product.

Persistence and degradability

Assessment biodegradation and elimination (H2O)

Experience shows this product to be inert and non-degradable.

Bioaccumulative potential

Bioaccumulation potential

The product will not be readily bioavailable due to its consistency and insolubility in water.

Additional information

Add. remarks environm. fate & pathway:

Due to the consistency of the product, dispersion into the environment is impossible. Therefore no negative effects on the environment may be anticipated based on the present state of knowledge.

Safety Data Sheet

Ultramid® C33

Revision date : 2021/09/21
Version: 3.0

Page: 7/8
(30509850/SDS_GEN_CA/EN)

13. Disposal considerations

Waste disposal of substance:

Check for possible recycling. Dispose of in accordance with national, state and local regulations.

Container disposal:

Dispose of in accordance with national, state and local regulations. Packs must be completely emptied. Completely emptied packagings can be given for recycling.

14. Transport Information

Land transport

TDG

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical DSL, CA released / listed

NFPA Hazard codes:

Health: 1 Fire: 1 Reactivity: 0 Special:

16. Other Information

SDS Prepared by:

BASF NA Product Regulations
SDS Prepared on: 2021/09/21

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

Safety Data Sheet

Ultramid® C33

Revision date : 2021/09/21
Version: 3.0

Page: 8/8
(30509850/SDS_GEN_CA/EN)

Ultramid® C33 is a registered trademark of BASF Canada or BASF SE
END OF DATA SHEET